

SERVICING REPORT GROUNDWATER SUMMARY

The form is to be completed by the Professional that prepared the Servicing Report.

Use of the form by the City of Toronto is not to be construed as verification of engineering/hydrological content.

For City Staff Use Only:	
Name of ECS Case Manager (please print)	
Date Review Summary provided to	

tolw			
A. SITE INF	ORMAITON	in SR (reference page number)	Report Includes this information City staff (Check)
Date Servicing Report was prepared:	2023-02-13	Pg.i	
Title of Servicing Report: Functional Servicing and Stormwater Management Report		Pg. i	
Name of Consulting Firm that prepared Servicing Report: Lithos Group Inc.		Pg. i	
Site Address	48 Grenoble Drive	Pg. iii	
Postal Code	M3C 1C8	Pg. 1	
Property Owner (identified on planning request for comments memo)	Tenblock	Pg. iii	
Proposed description of the project (ex. number of point towers, number of podiums, etc.)	The proposed residential development will consist of a 6-storey podium with two (2) high-rise, 39-storey towers	Pg. 2	
Land Use (ex. commercial, residential, mixed, industrial, institutional) as defined by the Planning Act	Residential-Use.	Pg. 1	
Number of below grade level	Two (2) underground levels.	Pg. 2	



Does the SR include a private water drainage system (PWDS)? PWDS: Private Water Drainage System: A subsurface drainage system which may consist of but is not limited to weeping tile(s), foundation drain(s), private water collection sump(s), private water pump or any combination thereof for the disposal of private water on the surface of the ground or to a private sewer connection or drainage system for disposal in a municipal sewer.	(Each of these PWDS may require a separate Toronto Water agreement) If No skip to Sections C (On-site Groundwater Containment) and/or D (Water Tight Requirements) as applicable	○ YES ✔ NO	
B. INFORMATION RELAT	ING TO GROUNDWATER	in SR (reference page number)	Report Includes this information City Staff (Check)
A copy of the pump schedule(s) for ALL groundwater sump pump(s) for the development site has been included in the FSR or A letter written by a Mechanical Consultant (signed and stamped by a Professional Engineer of Ontario) shall be attached to the SR stating the peak flow rate of the groundwater discharge for the development site for all groundwater sump pump(s). This peak flow rate must be based on the pump schedule(s) that have been designed by the Mechanical Consultant. A template of this letter is attached in Schedule A.			(CITCUI)
If there is more than one sump they must ALL be included in the letters along with a combined flow			



Is it proposed that the groundwater from the development site will be discharged to the sanitary, combined or storm sewer?	Sanitary Sewer Only during construction Combined Sewer Storm Sewer	Pg. 10	
Will the proposed PWDS discharge from the site go to the Western Beaches Tunnel (WBT)? *Reference attached WBT drainage map*			
What is the street name where the receiving sewer is located?	Grenoble Drive	Pg. 10	
What is the diameter of the receiving sewer?	375mm sanitary sewer	Pg. 10	
Is there capacity in the proposed local sewer system? YES NO	Are there any improvements required to the sewer system? If yes, identify them below and refer to the section and page number of the FSR whers information can be found. No improvements required If a sewer upgrade is required, the owner is required to enter into an Agreement with the City to improve the infrastructure? YES	Pg. 10	
Total allowable peak flow rate during a 100 year storm event (L/sec) to storm sewer When groundwater is to be discharged to the storm sewer the total groundwater and stormwater discharge shall not exceed the permissible peak flow rate during a 2 year pre development storm event, as per the City's	28.4 L/sec No groundwater is being discharged into the City's network.	Pg. 6	



Wet Weather Flow Management Guidelines, dated 2006			
Short-Term Groundwater Discharge Provide proposed total flow rate to the sanitary/combined sewer in post-development scenario Total Flow (L/sec) = sanitary flow + peak short-term groundwater flow rate	Short-term groundwater will be discharged into the City's sanitary network. Sanitary flow during construction = 0 L/sec Groundwater flow during construction (short-term groundwater discharge) = 2.85 L/s	Pg. 10	
Long-Term Groundwater Discharge Provide proposed total flow rate to the sanitary/combined sewer in post-development scenario Total Flow (L/sec) = sanitary flow + peak long-term groundwater flow rate	Not Applicable Proposed development will be water-tight	Pg. 10	
Does the water quality meet the receiving sewer Bylaw limits? YES NO	If the water quality does not meet the applicable receiving sewer Bylaw limits and the applicant is proposing a treatment system the applicant will need to include a letter stating that a treatment system will be installed and the details of the treatment system will be included in the private water discharge application that will be submitted to TW EM&P.	Pg.10	
C. ON-SITE	GROUNDWATER CONTAINMENT	Included in SR (reference page number)	Report Includes this information City Staff (Check)



How is the site proposing to manage th groundwater discharge on site?	e		N/A	
groundwater diserialize on site.				
Has the above proposal been approved by:	And And O	TW-WIM TW-EM&P ECS		
If the site is proposing a groundwater infiltration gallery, has it been stated that the groundwater infiltration gallery will not be connected to the municipal sewer? A connection between the infiltration gallery/dry well and the municipal sewer is not permitted Please be advised if an infiltration gallery/dry well on site is not connected to the municipal sewer, the site <u>must</u> submit two letters using the templates in Schedule B and Schedule C.	0	YES	N/A	
Confirm that the infiltration gallery can infiltrate 100% of the expected peak groundwater flow year round, ensure that the top of the infiltration trench is below the frost line (1.8m depth), not less than 5 m from the building foundation, bottom of the trench 1m above the seasonally high water table, and located so that the drainage is away from the building.			N/A	



SERVICING REPORT GROUNDWATER SUMMARY

D. WATER TIGHT REQUIREMENTS	Included in SR (reference page number)	Report Includes this information City Staff
		(Check)
If the site is proposing a water tight structure:		
1. The owner must submit a letter using the template in Schedule D.		Appendix B
2. A Professional Engineer (Structural), licensed to practice in Ontario and qualified in the subject must submit a letter using the template in Schedule E.		

Provide a copy of the approved SR to Toronto Water Environmental Monitoring & Protection Unit at pwapplication@toronto.ca.

Consulting Firm that prepared Servicing Report:	Lithos Group Inc.	ccccio.
Professional Engineer who completed the report summary:	Nick Moutzouris Print Name	N. MOUTZOURIS 100176986
Professional Engineer who completed the report summary:	Signature	Date & Stamp



March 18, 2022

Attention:

Chief Engineer and Executive Director, Engineering and Construction Services c/o Manager, Development Engineering 55 John Street, 16th Floor Toronto, ON M5v 3C6

CC:

General Manager, Toronto Water c/o Manager, Environmental Monitoring and Protection Unit 30 Dee Ave, Toronto ON M9N 1S9

Re: 48 Grenoble Drive, Toronto, ON

Our Project No. 22.161

Dear Sir or Madam,

I, Anthony Mirvish, confirm that all buildings on the subject lands (48 Grenoble Drive) can be constructed water-tight below grade in a manner that will resist hydrostatic pressure without any necessity for Private Water Drainage System (subsurface drainage system) consisting of but not limited to weeping tile(s), foundation drain(s), private water collection sump(s), private water pump or any combination thereof for the disposal of private water on the surface of the ground or to a private sewer connection directly or indirectly or drainage system for disposal directly or indirectly in a municipal sewer.

Sincerely,

Honeycomb Group Inc.

Anthony Mirvish, P. Eng.

Principal

anthony.mirvish@honeycombaroup.ca

416-451-9806





Microbjo Properties Inc. c/o Tenblock 30 Soudan Avenue, Suite 200 Toronto, ON M4S 1V6

March 18, 2022

Attention: Chief Engineer and Executive Director, Engineering and Construction Services c/o Manager, Development Engineering
Metro Hall
55 John Street, 16th Floor
Toronto ON M5V 3C6

cc: General Manager, Toronto Water c/o Manager, Environmental Monitoring and Protection Unit 30 Dee Ave, Toronto ON M9N 1S9

Dear Sir or Madam,

I, Tenblock, confirm and undertake that I will construct and maintain all building(s) on the subject lands (48 Grenoble Drive) in a manner which shall be completely water-tight below grade and resistant to hydrostatic pressure without any necessity for Private Water Drainage System (subsurface drainage system) consisting of but not limited to weeping tile(s), foundation drain(s), private water collection sump(s), private water pump or any combination thereof for the disposal of private water on the surface of the ground or to a private sewer connection directly or indirectly or drainage system for disposal directly or indirectly in a municipal sewer.

Sincerely,

Tenblock

Matthew Kelling, Development Manager

Mullely

mkelling@tenblock.ca

I, Matthew Kelling, have the authority to bind the corporation.



Smith + Andersen

1100 – 100 Sheppard Ave. East, Toronto ON, M2N 6N5 416 487 8151 f 416 487 9104 smithandandersen.com

2022-03-15

Attention: Chief Engineer and Executive Director, Engineering and Construction Services c/o Manager, Development Engineering

cc: General Manager, Toronto Water c/o Manager, Environmental Monitoring and Protection Unit 30 Dee Ave. Toronto ON M9N 1S9

Dear Sir or Madam,

I Vadim Vatoutine, confirm that all building(s) on the subject lands 48 Grenoble Dr. will be designed and constructed in a manner without Private Water Drainage System (subsurface drainage system) consisting of but not limited to weeping tile(s), foundation drain(s), private water collection sump(s), private water pump or any combination thereof for the disposal of private water on the surface of the ground or to a private sewer connection directly or indirectly or drainage system for disposal directly or indirectly in a municipal sewer. Underground structure(s) of the proposed building(s) will be built completely watertight without any direct or indirect connection to the City sewer for the discharge of groundwater (from a PWDS or floor drain or other infrastructure).

I understand that a Private Water Drainage System as an emergency back up system is not permitted, as part of this proposal.

Yours truly,

SMITH + ANDERSEN



Vadim Vatoutine, P.Eng. Senior Project Manager

21729.002.m. - 48 Grenoble Dr - GW Letter.docx